



Type	Displacement cm ³ /rev	Flow		Pressure P _{nom} bar	max Speed n rpm	Dimension												
		at 1500 rpm l/min	at max rpm l/min			Inlet			Outlet									
						A mm	B mm	E mm	F mm	d mm	E mm	F mm	d mm					
20A(C)4,5X021	4,5	6,14	14,33	250	3500	39,8	78	40	15	M6-6H	35	15	M6-6H					
20A(C)6,3X021	6,3	8,69	20,29	250	3500	41	81											
20A(C)8,2X021	8,2	11,32	26,40	250	3500	43,1	83,9											
20A(C)10X021	10	13,95	32,55	250	3500	47,5	87											
20A(C)11X021	11,3	15,76	36,78	250	3500	47,5	89,1											
20A(C)12X021	12	16,92	39,48	250	3500	47,5	90,3											
20A(C)14X021	14	19,95	46,55	250	3500	47,5	93,4											
20A(C)15X021	15	21,60	36,00	250	2500	47,5	94,9											
20A(C)16X021	16	23,04	38,40	250	2500	47,5	96,6											
20A(C)19X021	19	27,36	45,60	200	2500	47,5	101,5											
20A(C)22X021	22	31,68	42,24	180	2000	55	106,5											
20A(C)25X021	25	36,00	48,00	160	2000	57,2	111,4							40	20			