



Type	Displacement cm ³ /rev	Flow		Pressure P _{nom} bar	max Speed n rpm	Dimension							
		at 1500 rpm l/min	at max rpm l/min			A mm	B mm	Inlet			Outlet		
								E	F	d	E	F	d
20A(C)4,5X158	4,5	6,14	14,33	250	3500	39,8	85,2	40	15	M6-6H	35	15	M6-6H
20A(C)6,3X158	6,3	8,69	20,29	250	3500	41	88,2						
20A(C)8,2X158	8,2	11,32	26,40	250	3500	43,1	91,1						
20A(C)10X158	10	13,95	32,55	250	3500	47,5	94,1						
20A(C)11X158	11,3	15,76	36,78	250	3500	47,5	96,2						
20A(C)12X158	12	16,92	39,48	250	3500	47,5	97,5						
20A(C)14X158	14	19,95	46,55	250	3500	47,5	100,6						
20A(C)15X158	15	21,60	36,00	250	2500	47,5	102,1						
20A(C)16X158	16	23,04	38,40	250	2500	47,5	103,8						
20A(C)19X158	19	27,36	45,60	200	2500	47,5	108,7						
20A(C)22X158	22	31,68	42,24	180	2000	55	113,7						
20A(C)25X158	25	36,00	48,00	160	2000	57,2	118,5						