



Type	Displacement cm ³ /rev	Flow		Pressure P _{nom} bar	max Speed n rpm	Dimension							
		at 1500 rpm l/min	at max rpm l/min			A mm	B mm	Inlet			Outlet		
								M	G	U	M	G	U
20A(C)4,5X554...	4,5	6,14	14,33	250	3500	41,4	79,6	M20x1,5	G1/2	1 1/16"-12UNF	M16x1,5	G1/2	7/8"-14UNF
20A(C)6,3X554...	6,3	8,69	20,29	250	3500	42,6	82,6						
20A(C)8,2X554...	8,2	11,32	26,40	250	3500	44,7	85,5						
20A(C)10X554...	10	13,95	32,55	250	3500	49,1	88,6		G3/4				
20A(C)11X554...	11,3	15,76	36,78	250	3500	49,1	90,7						
20A(C)12X554...	12	16,92	39,48	250	3500	49,1	91,9		M20X1,5				
20A(C)14X554...	14	19,95	46,55	250	3500	49,1	95						
20A(C)15X554...	15	21,60	36,00	250	2500	49,1	96,5		G1/2				
20A(C)16X554...	16	23,04	38,40	250	2500	49,1	98,2						
20A(C)19X554...	19	27,36	45,60	200	2500	49,1	103,1		G1/2				
20A(C)22X554...	22	31,68	42,24	180	2000	56,6	108,1						
20A(C)25X554...	25	36,00	48,00	160	2000	58,8	113		G1/2				
20A(C)14X554H...	14	20,16	47,04	250	3500	55,3	105,7				M20x1,5		
20A(C)15X554H...	15	21,60	43,20	250	3000	55,6	106,8						
20A(C)16X554H...	16	23,04	46,08	250	3000	56,5	108,4						
20A(C)17,3X554H...	17,3	24,91	49,82	230	3000	57,6	110,5	G3/4					
20A(C)18,2X554H...	18,2	26,21	52,42	210	3000	58,4	112,1						
20A(C)19X554H...	19	27,36	54,72	200	3000	59	113,4	M20X1,5					
20A(C)22X554H...	22	31,68	52,80	180	2500	61,5	118,4						
20A(C)25X554H...	25	36,00	60,00	160	2500	63,9	123,3	G1/2					
20A(C)28X554H...	28	40,32	67,20	130	2500	66,4	128,1						
20A(C)32X554H...	32	46,08	61,44	120	2000	69,6	134,4	G3/4					
20A(C)36X554H...	36	51,84	69,12	100	2000	72,8	141						